



Husqvarna S 36

S 36 is a very powerful single-phase HEPA dust extractor to match the grinding machines Husqvarna PG 530 (1-phase), PG 450, PG 400 and PG 280 as well as small to mid size scarifiers, grinders, shot blasters and handheld power tools. This professional dust extractor is designed to meet strict demands. Three large, commercial-grade vacuum motors provide plenty of power. Equipped with three independently tested and certified HEPA H13 filters and a massive cone-shaped pre-filter with over 4.5 m² of media. This results in superior dust collection, even of fine sanding and gypsum dust. Features include Jet Pulse pre-filter cleaning, hour counter and vacuum meter for filter control. The non-marking wheels are puncture free and lock at the front. The Longopac[®] bag hose system ensures simple, dust-free bag changes.



Durable design

Corrosion-resistant steel clamps, welded frame with dust bag platform and durable steel handle make it ready to serve for many years.



Easy and efficient filter cleaning

The Jet Pulse filter cleaning system ensures high continuous airflow thanks to easy and efficient cleaning of the conical main filter without opening the machine.

Efficient filtration system

The three separate filtering stages result in longer working time between filter cleaning. The dust is filtered through a cyclone chamber, which separate the heaviest parts, up to 95% of the dust, before the washable main filter. The HEPA micro filters are individual tested and certified to capture 99.99% of the remaining silica dust in the respirable fraction (0.3µm).



Easy to transport

The welded frame enables easy transportation by resting the machine on the frame.



FEATURES

- Efficient filtration system
- Easy and efficient filter cleaning
- Durable design
- Easy to transport
- High Efficiency Particulate Air filter
- Easy-to-read airflow monitoring
- Clean and simple bag change
- For demanding industrial applications
- Control

Technical Specifications

MOTOR	
Fases	1~
Voltaje	230 V
Corriente nominal, A	15.7 A
Vacio máx.	220 mbar
Diámetro máximo de brocas, manual	3.6 kW
Máx. profundidad de corte	1500 mm
Máx. profundidad de corte	830 mm
Máx. profundidad de corte	620 mm
Peso	63 kg
ESPECIFICACIONES	
Air Flow	600 m ³ /h
HEPA filters 99.99% at 0.3 microns	3
Vacio máx.	220 mbar
Water lift	90 pulg
EMBALAJE	
Packaging length	820 mm
Packaging width	620 mm
Packaging height	1520 mm
Packaging volume	772.8 dm ³

ACCESSORIES



HUSQVARNA PG 530
965 19 58-12



HUSQVARNA PG 450
967 64 86-04



HUSQVARNA PG 280
967 27 82-08